


This document has been prepared by OBS GRAPHICS, KOLKATA, INDIA. This document is exclusive property of OBS GRAPHICS Unauthorized communication

OBS GRAPHICS						
	DATA SHEET OF HOSE REEL DRUM ASSEMBLY	PREPARED	MB	DOC. NO.: OBS/HRDA/01		
		CHECKED	KM	CONTRACT NO.:		
		APPROVED	PB	SHEET	1 OF 1	
		DATE		EQPT. NO.		
CLIENT:			PROJECT:			
SERVICE: FIRE HYDTANT & SPRINKLER SYSTEM		OPERATING MODE: CONTINIIOUS / INTERMITTEN		SITE:		
LOCATION: INDOOR / OUTDOOR		AREA CLASSIFICATION: HAZARDOUS-/ NON HAZARDOUS				
NUMBER REQUIRED: AS PER BILL OF QUANTITIES						
HOSE REEL DRUM ASSEMBLY						
	TECHNICAL PARAMITERS	DESCRIPTION				
1	CODE/STD	IS: 884				
2	TYPE	SWING TYPE POWDER COATED WALL MOUNTED				
3	OVER ALL HOSE REEL SIZE IN MM	DRUM DIA 600 MM (APPROX.)				
4	DRUM FINISH	POWDER COATED FINISH WITH P.O. RED COLOUR				
5	HOSE	RUBBER (MAKE - FIRE MARSHAL) / ISI MARKED				
6	SIZE	19 MM				
7	LENGTH OF HOSE	30 M				
8	WORKING PRESSURE	10.0 KG/CM2				
9	TEST PRESSURE	15KG/CM2				
10	BURSTING PRESSURE	48 KG/CM2				
11	STOP VALVE (BALL)	G.M.				
12	SIZE	25 MM				
13	NOZZLE					
b)	BODY MATERIAL	GM				
d)	OUT LET BORE	5 MM Ø				
e)	FLOW RATE OF NOZZLE(MM)	28 LPM				
14	MAKE	NEW AGE / SRI / ZENITH				
G.A. DRG. NO.		VENDOR				
FLOW DIAG. NO.		VENDOR DRG. NO.				
PLANT LAYOUT DRG. NO.		FOUNDATION DRG.NO.				
SUPPORT DRG. NO.		CALCULATION SHEET NO.				
ORDER NO.						
P0	ISSUED FOR APPROVAL	OBS	PB			
REV	DESCRIPTION	BY	APPROVED	CLIENT APP	DATE	

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41

